



CIAS 07 HV  
 CIAS 09 HV  
 CIAS 12 HV  
 CIAS 15 HV  
 CIAS 18 HV  
 CIAS 24 HV



WI-FI USB optional



7K - 9K - 12K



15K



18K



24K



MODELLO			CIAS 07 HV	CIAS 09 HV	CIAS 12 HV	CIAS 15 HV	CIAS 18 HV	CIAS 24 HV
<b>Dati prestazionali</b>								
Potenza resa RAFF	nom (min~max)	kW	2	2,7(0,8-3,4)	3,6(1-4,2)	4,4(1,3-5)	5,2(1,3-6,8)	7(2,2-8,5)
Potenza resa RISC	nom (min~max)	kW	2,3	2,8(1-4,6)	3,7(1,1-5,4)	5,4(1,4-6,0)	5,8(1,4-6,9)	7,5(2,4-9,8)
Pdesign RAFF	capacità (35°)	kW	2,7	2,7	3,6	4,4	5,2	7
Pdesign RISC	capacità (-10°)	kW	2,5	2,4	3,2	3,5	4,9	5,6
Alimentazione		V-Ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50	230-1-50	230-1-50
Volume aria trattato		m³/h	600	600	650	800	900	1200
<b>Unità interna</b>								
Potenza sonora		dB	52	52	54	55	57	62
Pressione sonora		dB(A)	39/34/27/21	39/34/27/21	40/35/31/22	44/40/35/28	44/43/37/30	47/43/37/35
Dimensioni	L x P x H	mm	855x204x280	855x204x280	855x204x280	900x210x310	997x235x322	1115x248x336
Peso netto		kg	10	10	10	11,5	13	15,3
<b>Dati idraulici</b>								
Tubazione liquido Ø		mm	6,35	6,35	6,35	6,35	6,35	9,52
Tubazione gas Ø		mm	9,52	9,52	9,52	9,52	12,7	15,88