



CIAB 09 CS  
 CIAB 12 CS  
 CIAB 18 CS  
 CIAB 24 CS



9K                      12K                      comando di serie



CIAB 09 CS



CIAB 12 CS



YR-HD01

18K                      24K



CIAB 18 CS



CIAB 24 CS

Modello	UI		CIAB 09 CS	CIAB 12 CS	CIAB 18 CS	CIAB 24 CS
<b>Dati prestazionali</b>						
Potenza resa RAFF	nom (min-max)	kW	2,6	3,5 (0,9-4,5)	5 (1,8-5,8)	7,1 (2-7,3)
Potenza resa RISC	nom (min-max)	kW	2,9	3,7 (1-4,8)	5,2 (2-6,5)	7,1 (2,5-8)
Pdesign RAFF	capacità (35°)	kW	/	3,5	5	7,1
Pdesign RISC	capacità (-10°)	kW	/	3,4	4,7	5,2
Alimentazione		V-Ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50
Volume aria trattato		m³/h	620/520/450	620/520/450	700/620/500	1300/1100/870
<b>Unità interna</b>						
Potenza sonora		dB	50/46/42	50/46/42	55/50/47	59/57/52
Pressione sonora		dB(A)	40/36/32	40/36/32	42/37/35	46/44/39
Dimensioni	L x P x H	mm	570x570x260	570x570x260	570x570x260	840x840x240
Peso netto		kg	17	18,5	18,5	25,5
Dimensioni pannello	L x P x H	mm	700x700x60	700x700x60	700x700x60	950x950x60
Peso netto pannello		kg	2,8	2,8	2,8	2,8
<b>Dati idraulici</b>						
Tubazione liquido Ø		mm	6,35	6,35	6,35	9,52
Tubazione gas Ø		mm	9,52	9,52	12,7	15,88